

**Product Data Sheet**

**PATIO JOINTING REPAIR**

**PATIO JOINTING REPAIR**

**Description**

**Patio Jointing Repair** is a conveniently packaged mortar made from Portland cement and high quality aggregates and additives. The product is supplied in a convenient tub that can be used for mixing the mortar. The tub also makes transportation a clean and easy process.

**Uses**

**Patio Jointing Repair** is a convenient method for repointing crumbling joints between paving slabs. It can be used to repair joints up to 2mm wide. It can also be used under slabs as a bedding material.

**Special Properties**

- Supplied in a convenient tub for mixing the mortar
- Easy to use – requires no special skills
- Prevents weed growth in garden paths
- For exterior use only
- Trade formulation

**Yield**

Each 10kg tub will produce enough mortar for around 3 standard slabs dependant on the width of the joint.

These figures are approximate and take no account for site wastage.

**Tools Required**

The following tools are required for the job:

- Gloves
- Googles
- Chisel
- Hammer
- Stiff Brush
- Scissors
- Measuring Jug
- Soft Brush
- Builders Trowel
- Water Sprayer



**Mixing and Usage Instructions**

1. Remove old mortar using a cold chisel and club hammer. For particularly stubborn joints you can use a hammer drill with a chisel attachment but take care not to damage the slabs. Wear gloves and goggles.
2. Remove any loose debris with a stiff brush.
3. Open the tub and pour the contents of the u-can sachets as required.
4. Gradually add water to the powder (be careful that you do not add too much). When the mortar is a damp enough to roll into a ball it is ready to be used.
5. Press the mortar into the joint using a builder trowel pushing down firmly so there are no gaps underneath.
6. Remove excess mortar from slabs immediately to avoid staining.
7. Smooth off roughly level with the flagstones using the rounded end of the trowel to create a slight indent.
8. Spray the joints with water and leave to set. It also recommended that the joints be protected from winds and direct sunlight using a plastic sheet or hessian.
9. The recommended application temperature is 5° to 25°C.

## Packaging and Storage

**Patio Jointing Repair** is available in nominal 10kg tubs.

**Patio Jointing Repair** should be stored in cool dry areas clear of the ground.

The product should be used on a first in – first out basis.

Shelf life is 12 months from the date of manufacture as printed on the bag.

## Quality Control

All Tarmac Building Products are factory blended, tested and packaged to quality control procedure in accordance with BS EN ISO 9001.

## Clean up and Spillages

Dry powders should be swept up and disposed of in accordance with the Local Authority.

## HEALTH AND SAFETY

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet. Users are advised to wear face mask, goggles, gloves and overalls when handling, mixing and applying cementitious products.

Contains Portland Cement. Contains Chromium (VI), which may produce an allergic reaction. Clothing contaminated by wet cement should be removed immediately and washed before reuse. R38 - Irritating to skin. R41 - Risk to serious damage to eyes. S26 - In case of contact with eyes, rinse immediately with water and seek medical advice. S37/39 - Wear suitable gloves and eye/face protection. S2 - Keep out of reach of children.

## Information, Prices & Ordering

For technical information, pricing and to place orders please contact us as follows:

Technical Information t: **08444 63 00 46**

Orders t: **Exclusively through B&Q**

Email: **u-can@tarmacbp.co.uk**

Visit our website: **u-can.tv**

Tarmac Building Products Ltd., Salisbury House, 2A Tettenhall Road, Wolverhampton, WV1 4SA

Use of the 'Tarmac' name and the T symbol is under licence from Lafarge Tarmac Trading Limited. 'Tarmac' and the T symbol are registered trademarks. Registered in England No. 4026569. Registered office: Salisbury House, 2a Tettenhall Road, Wolverhampton WV1 4SA.

Although we try to ensure that the information in this publication is accurate, it is not intended as technical advice applicable to your particular circumstances and we accept no liability if you use it in this way.

**Warning:** The advice shown on this sheet is given as a guide to good practice but Tarmac Building Products can accept no responsibility for any loss, damage or injury howsoever caused in following it.